

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)


PCT

(10) International Publication Number
WO 2004/015909 A1

- (51) International Patent Classification⁷: **H04L 1/00** (74) Agents: GEARY, Stuart et al.; Venner, Shipley & Co., 20 Little Britain, London EC1A 7DH (GB).
- (21) International Application Number: PCT/EP2002/008587
- (22) International Filing Date: 1 August 2002 (01.08.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BYSTED, Tommy, Kristensen [DK/DK]; Askeaaen 4, DK-2765 Smørum (DK). PEDERSEN, Kent [DK/DK]; Borups Alle 109 3.th, DK-20000 Frederiksberg (DK). SEBIRE, Benoist [FR/FI]; Sateentie 4, FIN-02100 Espoo (FI).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TRANSMITTING INTERLEAVED MULTIPLE DATA FLOWS



(57) Abstract: Multiple transport channels (405, 406, 407) are multiplexed and transmitted in a single physical channel. A code (TFCI) is added to the transport channel data flows to indicate which processing schemes, from a set of available schemes, are being employed and the resultant blocks are interleaved. The depth of the interleaving is set in dependence on the transmission time intervals associated with the schemes in the set of processing schemes.